

# SAFETY DATA SHEET

[in accordance with the criteria of Regulation no 1907/2006 (REACH) as amended]

#### Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

#### **BORE CLEANING FOAM**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: cleaning agent, removes deposits and other impurities (carbon, dust, carbon

deposits, etc.).

<u>Uses advised against:</u> not determined.

# 1.3 Details of the supplier of the safety data sheet

Supplier:

Address:

Telephone number:

E-mail address for a competent person responsible for SDS:

1.4 Emergency telephone number

112

#### Section 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Aerosol 1 H222-H229, Skin Irrit. 2 H315, Eye Dam. 1 H318

Extremely flammable aerosol. Pressurised container: May burst if heated. Causes skin irritation. Causes serious eye damage.

#### 2.2 Label elements

Hazard pictograms and signal words





DANGER

# Names of substances mentioned on the label

Contains: 2-aminoethanol.

#### **Hazard statements**

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

H318 Causes serious eye damage.

# Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P410+P412 Protect from sunlight. Do no expose to temperatures exceeding 50°C/ 122°F.

P501 Dispose of contents/container to properly labelled waste containers according to national law.



#### 2.3 Other hazards

Substance does not meet criteria for PBT or vPvB in accordance with Annex XIII of Regulation REACH. The components of the mixture are not identified as having endocrine disrupting properties.

#### Section 3: Composition/information on ingredients

#### 3.1 Substances

Not applicable.

#### 3.2 Mixtures

CAS: 106-97-8	butane <sup>1</sup>	
EC: 203-448-7	Flam. Gas 1 H220, Press. Gas H280	10-20 %
Index number: 601-004-00-0		10-20 %
Registration number: -		
CAS: 74-98-6	propane	
EC: 200-827-9	Flam. Gas 1 H220, Press. Gas H280	5-10 %
Index number: 601-003-00-5		3-10 %
Registration number: -		
CAS: 141-43-5	2-aminoethanol <sup>1,2</sup>	
EC: 205-483-3	Acute Tox. 4 H302, Acute Tox. 4 H312, Skin Corr. 1B H314, Eye Dam. 1	
Index number: 603-030-00-8	H318, Acute Tox. 4 H332, STOT SE 335	< 5 %
Registration number:	Specific concentration limit:	
01-2119486455-28-XXXX	STOT SE 3 H335: C ≥ 5 %	
CAS: 57-55-6	1,2-propanodiol <sup>1</sup>	
EC: 200-338-0	the substance is not classified as hazardous	
Index number: -		1-3 %
Registration number:		
01-2119456809-23-XXXX		
CAS: 111-76-2	2-butoxyethanol <sup>1,2</sup>	
EC: 203-905-0	Acute Tox. 4 H302, Skin Irrit. 2 H315, Eye Irrit. 2 H319, Acute Tox. 3 H331	
Index number: 603-014-00-0	inhalation: ATE = 3 mg/L (Vapours)	1-3 %
Registration number:	oral: ATE = 1 200 mg/kg bw	
01-2119475108-36-XXXX		

<sup>1)</sup> Substance with occupational exposure limits defined on the national level.

#### Section 4: First aid measures

#### 4.1 Description of first aid measures

<u>Skin contact</u>: consult a doctor in case of any disturbing symptoms. Take off contaminated clothes. Thoroughly wash the exposed skin areas with soap and water.

<u>Eye contact</u>: seek medical advice immediately. Protect non-irritated eye, remove any contact lenses. Wash out with plenty of water for 10-15 min. Avoid strong stream of water – risk of damage of the cornea. Put on a sterile dressing.

<u>Ingestion:</u> exposure by this route usually does not occur. If swallowed, rinse mouth with water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Consult a doctor, show the packaging or label.

Inhalation: remove the victim to fresh air, keep warm and calm. Consult a doctor if disturbing symptoms appear.

# 4.2 Most important symptoms and effects, both acute and delayed

Eye contact: possible redness, tearing, burning sensation, pain, risk of eye damage.

Skin contact: prolonged contact may cause skin dryness, cracking, irritation.

<u>Inhalation</u>: high concentration of vapours may cause nausea, dizziness, drowsiness, coordination disorders <u>Ingestion</u>: exposure by this route does not occur.

<sup>2)</sup> Substance with occupational exposure limits defined on the Community level.

Full text of each relevant H phrase is in section 16.



# 4.3 Indication of any immediate medical attention and special treatment needed

Physician makes a decision regarding further medical treatment after thoroughly examination of the injured. Treat symptomatically.

# Section 5: Firefighting measures

# 5.1 Extinguishing media

Suitable extinguishing media: CO<sub>2</sub>, extinguishing powders, alcohol-resistant foam, water spray.

Unsuitable extinguishing media: water jet - risk of the propagation of the flame.

#### 5.2 Special hazards arising from the substance or mixture

During the fire, the product may produce harmful gases containing, e.g. carbon oxides and other unidentified thermal decomposition products. Do not inhale combustion products, they can be dangerous for human health.

#### 5.3 Advice for firefighters

Personal protection typical in case of fire. Do not stay in the fire zone without self-contained breathing apparatus and protective clothing resistant to chemicals. Extremely flammable aerosol. Pressurised container: May burst if heated. In case of fire cool endangered containers with water spray from safe distance. Collect used extinguishing media.

#### Section 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Limit the access for the outsiders into the breakdown area, until the suitable cleaning operations are completed. In case of large spills, isolate the exposed area. Ensure that removing the problem and its results is conducted by a trained personnel only. Ensure adequate ventilation, especially in the lower parts of premises. Explosion hazard zone; vapours are heavier than air and create explosive mixtures with air. Vapours may spread along the floor / ground to distant sources of ignition and pose a risk from flashback. Eliminate all sources of ignition - do not use an open flame, do not smoke, do not use sparking tools, etc. Use personal protective equipment. Avoid contact with skin and eyes.

#### 6.2 Environmental precautions

Do not allow the mixture to get into surface waters and soil. In case of release of large amounts of the product, it is necessary to take appropriate steps to prevent it from spreading into the environment. Notify relevant emergency services.

# 6.3 Methods and material for containment and cleaning up

Absorb leakage with liquid absorbing materials (e.g. sand, earth, universal binding agents) and place it in labeled containers. Bank up larger spills and pump them out. Use non-sparking tools. Treat collected material as waste. Clean and ventilate the contaminated area well.

#### 6.4 Reference to other sections

Appropriate conduct with waste product - see section 13. Personal protective equipment - see section 8.

#### Section 7: Handling and storage

# 7.1 Precautions for safe handling

Handle in accordance with good occupational hygiene and safety practices. Ensure adequate ventilation, do not inhale the vapours of the product. Avoid contact with skin and eyes. Keep unused containers tightly closed. Remove all sources of ignition, do not smoke. Avoid electrostatic discharge. Do not use sparking tools. Do not allow vapours to concentrate in the air and to create concentrations within the limits of explosive properties or exceeding the OEL.

# 7.2 Conditions for safe storage, including any incompatibilities

Store only in original, tightly closed containers, in a dry and well-ventilated place. Do not store with incompatible materials (see subsection 10.5). Keep away from food, beverages or feed for animals. Do not destroy, puncture or heat up empty containers. Avoid direct sunlight. Do not use open fire in the warehouse.



# SAFETY DATA SHEET

#### 7.3 Specific end use(s)

No information about other uses than those mentioned in subsection 1.2.

# Section 8: Exposure controls/personal protection

#### 8.1 Control parameters

Specification	TWA 8 hour	STEL 15 min
1,2-propanodiol [CAS 57-55-6]		
total vapour and particulates	474 mg/m³	-
particulates	10 mg/m³	-
butane [CAS 106-97-8]	1450 mg/m³	1810 mg/m <sup>3</sup>
2-aminoethanol [CAS 141-43-5]	2,5 mg/m <sup>3</sup>	7,6 mg/m <sup>3</sup>
2-butoxyethanol [CAS 111-76-2]	123 mg/m³	246 mg/m <sup>3</sup>

Legal basis: EH40/2005 (Fourth Edition 2020)

#### Recommended control procedures

Procedures concerning the control over the dangerous components concentrations in the air and control over the air quality in the workplace – if they are available and justified for the position – in accordance with the European Standards, with the conditions within the exposure place and a proper test methodology adapted to the working conditions.

#### DNEL

# 2-aminoethanol [CAS 141-43-5]

Worker, skin, long-term exposure, systemic effects: 1 mg/kg body weight/day

Worker, inhalation, long-term exposure, local effects 3,3 mg/m<sup>3</sup>

Consumer, oral, long-term exposure, systemic effects: 3,75 mg/kg body weight/day Consumer, skin, long-term exposure, systemic effects: 0,24 mg/kg body weight/day

Consumer, inhalation, long-term exposure, systemic effects: 2 mg/m<sup>3</sup> Consumer, inhalation, long-term exposure, local effects: 2 mg/m<sup>3</sup>

1,2-propanodiol [CAS 57-55-6]

Worker, inhalation, long-term exposure, local effects: 10 mg/m³
Worker, inhalation, long-term exposure, systemic effects: 168 mg/m³
Consumer, inhalation, long-term exposure, systemic effects: 20 mg/m³
Consumer, inhalation, long-term exposure, local effects: 10 mg/m³

#### **PNEC**

#### 2-aminoethanol [CAS 141-43-5]

freshwater 0,085 mg/l
marine water 0,0085 mg/l
freshwater sediment 0,425 mg/kg
marine water sediment o,0425 mg/l
soil 0,035 mg/kg
STP 0,085 mg/l

#### 1,2-propanodiol [CAS 57-55-6]

freshwater 260 mg/l 26 mg/l 26 mg/l 26 mg/l 572 mg/kg marine water sediment 57,2 mg/kg soil 50 mg/kg STP 20 000 mg/l



#### 8.2 Exposure controls

# Appropriate engineering controls

Use the product in accordance with good occupational hygiene and safety practices. Ensure adequate general and/or local ventilation to ensure the maintenance of concentrations of hazardous components in the air below the exposure limit values. Local exhaust is preferred because it removes contaminants from the point of their origin, preventing them from spreading. Do not eat, drink or smoke when using the product. Avoid contact with eyes and skin. If during work processes there is a risk of ignition of workers' clothing, safety showers and eye washes should be installed in the vicinity of the workplaces.

#### Personal protective equipment

The necessity to use and selection of appropriate personal protective equipment should take into account the type of risk posed by the product, working conditions and the way of handling the product. The personal protective equipment used must meet the requirements of Regulation (EU) 2016/425 and the relevant standards. The employer is obliged to provide protection measures appropriate to the activities performed and meeting all quality requirements, including their maintenance and cleaning. Any contaminated or damaged PPE must be replaced immediately.

#### Skin protection

Use appropriate protective gloves in accordance with EN 374. The material for gloves should be selected individually at the workplace. In case of a short contact, use protective gloves with effectiveness level 2 (breakthrough time > 30 min.). In case of a prolonged contact, use protective gloves with effectiveness level 6 (breakthrough time > 480 min.). Use protective clothing.

The material that the gloves are made of must be impenetrable and resistant to the product's effects. The selection of material must be performed with consideration of breakthrough time, penetration speed and degradation. Moreover, the selection of proper gloves depends not only on the material, but also on other quality features and changes depending on the manufacturer. The producer should provide detailed information regarding the exact breakthrough time. This information should be followed.

#### Eye protection

Wear safety glasses or face protection in accordance with EN 166.

# Respiratory protection

Under normal conditions it is not required. In case of the formation of vapours and aerosols, use absorbing equipment or absorbing and filtering equipment with a suitable protection class (class 1/protection against gases or vapours with a concentration in the air volume not exceeding 0.1%, class 2 / protection against gases or vapours with a concentration in the air not exceeding 0.5%, class 3 / protect against gases or vapours at concentrations in the air volume to 1%). In cases where the oxygen concentration is  $\leq$  19% and / or maximum concentration of toxic substances in the air is  $\geq$  1.0% by volume, isolating equipment should be used.

#### Thermal hazards

Do not occur.

#### **Environmental exposure controls**

Avoid environment contamination, do not empty into drains. Possible emissions from the ventilation systems and processing equipment should be controlled in order to determinate their compatibility with environmental protection regulations.

# Section 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Physical state: liquid in an aerosol container

Colour: colourless
Odour characteristic
Melting point/freezing point: not determined

Boiling point or initial boiling point

and boiling range: not determined

Flammability: extremely flammable aerosol

Lower and upper explosion limit: not determined Flash point: not determined

# **SAFETY DATA SHEET**

Auto-ignition temperature: not determined Decomposition temperature: not determined pH: not determined Kinematic viscosity: not determined Solubility: soluble in water

Partition coefficient n-octanol/water

(log value): not determined Vapour pressure: not determined

Density and/or relative density: 1 g/cm<sup>3</sup>

Relative vapour density: not determined Particle characteristics: not applicable

#### 9.2 Other information

No additional data.

# Section 10: Stability and reactivity

#### 10.1 Reactivity

Product is reactive. It does not undergo hazardous polymerization. Vapours can form explosive mixtures with air. See also subsections 10.3 and 10.5.

#### 10.2 Chemical stability

The product is stable under normal conditions of use and storage.

#### 10.3 Possibility of hazardous reactions

No hazardous reactions are known.

# 10.4 Conditions to avoid

Avoid source of fire, open flame, excessive heating, temperature above 50°C.

#### 10.5 Incompatible materials

Strong oxidizing agents, aluminum, acids.

#### 10.6 Hazardous decomposition products

Not known.

# Section 11: Toxicological information

# 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### **Toxicity of components**

2- aminoethanol [CAS 141-43-5]

 $LD_{50}$  (oral, rat) 1089 mg/kg  $LD_{50}$  (skin, rat) 2504 mg/kg

1,2-propanodiol [CAS 57-55-6]

 $LD_{50}$  (oral, rat) 22000 mg/kg  $LD_{50}$  (skin, rabbit) > 2000 mg/kg  $LC_{50}$  (inhalation, rabbit) 317042 mg/l/2h

2-butoxyethanol [CAS 111-76-2]

Acute toxicity estimate: ATE = 1200 mg/kg (oral) ATE = 3 mg/L (Vapours)

# **Toxicity of mixture**

Acute toxicity

ATE mix (oral) > 2000 mg/kg
ATE mix (skin) > 2000 mg/kg

# SAFETY DATA SHEET

ATE mix (inhalation)

 $> 20 \text{ mg/m}^3$ 

The acute toxicity estimate (ATEmix) for the classification of a substance in a mixture was determined using the appropriate conversion value from Table 3.1.2 Annex I to CLP as amended.

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

See subsection 4.2 for more information on the effects from each possible route of exposure.

Symptoms related to the physical, chemical and toxicological characteristics

No data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

No data.

#### 11.2 Information on other hazards

**Endocrine disrupting properties** 

The components of the mixture are not identified as having endocrine disrupting properties.

Other information

Not applicable.

# Section 12: Ecological information

# 12.1 Toxicity

# **Toxicity of components**

2- aminoethanol [CAS 141-43-5]

 $\begin{array}{lll} \mbox{Acute toxicity to fish $LC_{50}$} & 2070 \mbox{ mg/I/96h} \\ \mbox{Acute toxicity to crustaceans $EC_{50}$} & 32,6 \mbox{ mg/I/48h} \\ \mbox{Acute toxicity to algae $EC_{50}$} & 2,5 \mbox{ mg/I/72h} \\ \end{array}$ 

1,2-propanodiol [CAS 57-55-6]

Acute toxicity to fish  $LC_{50}$  40613 mg/I/96h/Oncorhynus mykiss Acute toxicity to crustaceans  $EC_{50}$  18340 mg/I/48h/Ceriodaphnia dubia

Acute toxicity to algae EC<sub>50</sub> 19000 mg/I/96h/Pseudokirchneriella subcapitata

# SAFETY DATA SHEET

# **Toxicity of mixture**

Product is not classified as hazardous for the environment.

#### 12.2 Persistence and degradability

No data.

#### 12.3 Bioaccumulative potential

No data.

#### 12.4 Mobility in soil

Product is mobile in water and soil environment. Gas components disperse rapidly in the air.

#### 12.5 Results of PBT and vPvB assessment

The components do not meet the criteria for PBT or vPvB in accordance with Annex XIII of REACH Regulation.

#### 12.6 Endocrine disrupting properties

The components of the mixture are not identified as having endocrine disrupting properties.

#### 12.7 Other adverse effects

The mixture is not classified as hazardous to the ozone layer. Consider other harmful effects of individual components of the mixture on the environment (eg, global warming potential).

#### Section 13: Disposal considerations

#### 13.1 Waste treatment methods

<u>Disposal methods for the product:</u> disposal in accordance with the local legislation. Do not dispose of with municipal waste. Do not mix with other waste. Waste code should be given in the place of waste formation.

<u>Disposal methods for used packing:</u> reuse/recycle/eliminate empty containers in accordance with the legislation in force. Do not pierce or burn, even after use. Only containers completely empty can be recycled.

Legal basis: Directive 2008/98/EC as amended, 94/62/EC as amended.

# Section 14: Transport information

#### 14.1 UN number or ID number

UN 1950

# 14.2 UN proper shipping name

ADR/RID

**AEROSOLS** 

IMDG

**AEROSOLS** 

ICAO/IATA

AEROSOLS, FLAMMABLE

#### 14.3 Transport hazard class(es)

2

Subclass: 2.1

# 14.4 Packing group

Not applicable.

#### 14.5 Environmental hazards

The product is not dangerous for environment in accordance with transport regulations.



#### 14.6 Special precautions for user

Packages shall not be thrown or subjected to impact. Receptacles shall be so stowed in the vehicle or container that they cannot overturn or fall. Avoid sources of ignition. While handling the product, wear personal safety clothing, as indicated in section 8.

#### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

#### Other informations

ADR	Limited quantities LQ	1 L
	Classification code	5F
	Transport category	2
	Tunnel restriction code	(D)
IMDG	Limited quantities LQ	1 L
	EmS code	F-D, S-U

# Section 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

**Regulation (EC) No 1907/2006** of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC as amended.

**Regulation (EC) No 1272/2008** of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 as amended.

**Commission Regulation (EU) No 2020/878** of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

**Directive 2008/98/EC** of the European Parliament and of the Council of 19 November 2008 on waste and repealing certain Directives as amended.

**European Parliament and Council Directive 94/62/EC** of 20 December 1994 on packaging and packaging waste as amended.

**Regulation (EU) 2016/425** of the European Parliament and of the Council of 9 March 2016 on personal protective equipment and repealing Council Directive 89/686/EEC as amended.

ADR Agreement concerning the International Carriage of Dangerous Goods by Road

**IMDG** Code International Maritime Dangerous Goods Code.

IATA Dangerous Goods Regulations.

**Commission Directive 2000/39/EC** of 8 June 2000 establishing a first list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work.

**Commission Directive 2006/15/EC** of 7 February 2006 establishing a second list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC and amending Directives 91/322/EEC and 2000/39/EC.

**Commission Directive 2009/161/EU** of 17 December 2009 establishing a third list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC and amending Commission Directive 2000/39/EC.

**Commission Directive 2017/164/EU** of 31 January 2017 establishing a fourth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC, and amending Commission Directives 91/322/EEC, 2000/39/EC and 2009/161/EU.

**Commission Directive 2019/1831/EU** of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC.

# 15.2 Chemical safety assessment

It is not necessary to carry out a chemical safety assessment for the mixture.

# Section 16: Other information

Full text of indicated H phrases mentioned in chapter 3

H220 Extremely flammable gas.

# SAFETY DATA SHEET

H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.
 H318 Causes serious eye damage.
 H319 Causes serious eye irritation.

H331 Toxic if inhaled. H332 Harmful if inhaled.

H335 May cause respiratory irritation.

#### Clarification of aberrations and acronyms

PBT Persistent, Bioaccumulative and Toxic substance vPvB very Persistent, very Bioaccumulative substance

Press. Gas
Flam. Gas 1
Eye Dam. 1
Eye Irrit. 2
Acute Tox. 3, 4
Skin Corr. 1B
Skin Irrit. 2
Gases under pressure
Flammable gas, category 1
Eye damage category 1
Eye irritation category 2
Acute toxicity category 3, 4
Skin corrosion category 1B
Skin Irrit. 2
Skin irritation category 2

STOT SE 3 Specific target organ toxicity — single exposure category 3

#### **Trainings**

Before commencing working with the product, the user should learn the Health & Safety regulations, regarding handling chemicals, and in particular, undergo a proper workplace training. Persons related to the transportation of the dangerous goods in compliance with the ADR Agreement should be properly trained within the scope of performed tasks (general training, on-the-job training and training related to the safety issues).

## Key literature references and data sources

The data sheet was prepared on the basis of the safety data sheets of individual components, literature data, online databases (e.g. ECHA, TOXNET, COSING) as well as our knowledge and experience, taking into account current legislation.

Methods of evaluating information which was used for the purpose of classification acc. Regulation (EC) No 1272/2008 as amended

Aerosol 1 H222-H229 manufacturer data
Eye Dam. 1 H318 calculation method
Skin Irrit. 2 H315 calculation method

Other data

Date of update: 13.01.2023 Changes: section 3

The information above is based on a current available data concerning the product, but also on the experience and knowledge in this field of the producer. They are neither a quality description of the product nor a guarantee of particular features. They are to be treated as aid to safety in transport, storage and usage of the product. That does not free the user from the responsibility of improper usage of the information above and also of improper compliance with the law norms in the field.